

MODEL

Access Platform Transporters GPT 26

Technical Information

As with all other machine specific trailers in our range, attention has been paid in manufacturing a trailer that is light, compact and easy to use for transporting small tracked access platforms up to 15m working heights.

A standard feature of this model is a height adjustable coupling this makes towing behind light vans possible with low tow bar heights, particularly if the tow vehicle is loaded.

All trailers are compliant with new trailer type approval regulations

Standard Features

- Heavy duty soft ride suspension axles
- Fully galvanised steel chassis
- Easy to use steel loading ramps included. With safety anti kick up feature
- Rear prop stands for loading when unhitched, anti slip type
- 18mm resin coated plywood floor
- 4 heavy duty lashing points
- Rope hooks
- Full road lighting in protective brackets including reverse lamps- commercial quality
- Industrial quality coupling fitted (ball or eye)
- Heavy duty jockey wheel
- 200mm auto-reverse brakes on all wheels
- Flat top steel mudguards to stand on
- 13 pin electric connection
- Adjustable coupling height feature

Optional Extras

- Bracket mounted spare wheel
- Bolt on track stops for tracked machines
- Ratchet load straps
- LED lighting, dual voltage
- Winch kit
- Insurance approved hitch lock/ wheel clamp



Compatible Machine Types

Hinowa 14.70 or similar machines up to 15m



	Deck size mm	payload	gross weight	brakes	wheel size
GPT 26	2500 X 1230	2150kg	2600kg	200 X 50mm	155/70 R12